

ALUMINIUM LIFTING BEAM



Aluminium Lifting Beam rigid with hooks on both faces

2 guide handles
Aluminium profile
Steel rigging equipment
Coated in orange

Order No.	Model	Carrying Capacity kg	Working Width mm	Total Construction Height mm	Suspension Eye mm	Weight kg
410 051	ATS 0.5-1	500	1,000	180 / 280	70 x 90	10
410 052	ATS 0.5-2	500	2,000	180 / 280	70 x 90	15
410 053	ATS 0.5-3	500	3,000	180 / 280	70 x 90	19
410 152	ATS 1.5-2	1,500	2,000	280 / 380	70 x 90	23
410 153	ATS 1.5-3	1,500	3,000	280 / 380	70 x 90	29
410 154	ATS 1.5-4	1,500	4,000	280 / 380	70 x 90	35



Aluminium Lifting Beam adjustable with 2 hooks

2 guide handles
Aluminium profile
Steel rigging equipment
Coated in orange

Order No.	Model	Carrying Capacity kg	Working Width min / max mm	Hole intervals mm	Total Construction Height mm	Suspension Eye mm	Weight kg
410 251	ATV 0.5-1	500	500 / 1,000	125	285 / 345	70 x 90	14
410 252	ATV 0.5-2	500	500 / 2,000	125	285 / 345	70 x 90	18
410 253	ATV 0.5-3	500	1,000 / 3,000	125	285 / 345	70 x 90	23
410 352	ATV 1.5-2	1,500	1,000 / 2,000	125	385 / 445	70 x 90	28
410 353	ATV 1.5-3	1,500	1,000 / 3,000	125	385 / 445	70 x 90	34
410 354	ATV 1.5-4	1,500	1,000 / 4,000	250	385 / 445	70 x 90	40

Aluminium Lifting Beam H rigid

with hooks on both faces

4 guide handles
Aluminium profiles
Steel rigging equipment
Coated in orange



Order No.	Model	Carrying Capacity kg	Working Length mm	Working Width mm	Total Construction Height mm	Suspension Eye mm	Weight kg
410 451	AHTS 0.5-1-1	500	1,000	1,000	80 / 305	70 x 90	32
410 452	AHTS 0.5-2-1	500	2,000	1,000	80 / 305	70 x 90	36
410 453	AHTS 0.5-3-2	500	3,000	2,000	80 / 305	70 x 90	49
410 552	AHTS 1.5-2-1	1,500	2,000	1,000	80 / 405	70 x 90	45
410 553	AHTS 1.5-3-2	1,500	3,000	2,000	80 / 405	70 x 90	60
410 554	AHTS 1.5-4-2	1,500	4,000	2,000	80 / 405	70 x 90	66

Aluminium Lifting Beam H adjustable

with 4 adjustable hooks

4 guide handles
Aluminium profiles
Steel rigging equipment
Coated in orange



Order No.	Model	Carrying Capacity kg	Working Length mm	Working Width mm	Teilung mm	Total Construction Height mm	Suspension Eye mm	Weight kg
410 651	AHTV 0.5-1-1	500	500 / 1,000	500 / 1,000	125	185 / 305	70 x 90	33
410 652	AHTV 0.5-2-1	500	500 / 2,000	500 / 1,000	125	185 / 305	70 x 90	37
410 653	AHTV 0.5-3-2	500	1,000 / 3,000	500 / 2,000	125	185 / 305	70 x 90	50
410 752	AHTV 1.5-2-1	1,500	1,000 / 2,000	500 / 1,000	125	185 / 405	70 x 90	46
410 753	AHTV 1.5-3-2	1,500	1,000 / 3,000	500 / 2,000	125	185 / 405	70 x 90	61
410 754	AHTV 1.5-4-2	1,500	1,000 / 4,000	500 / 2,000	250	185 / 405	70 x 90	67